

AS4705-700

SWITCH MONITOR MODULE



Product Overview

Product	Switch Monitor Module
Part No.	AS4705-700
Digital Communication	XP95 and Discovery

Product Information

The Switch Monitor Module is a loop-powered device incorporating a monitored input circuit for connection to remote switches, for indoor use only.

- Built-in Isolator
- Visible LEDs
- Loop Powered
- Ground fault detection
- Selectable priority to monitor equipment where a fast response is required
- Interrupt facility
- Improved design for ease of wiring

Technical Data

All data is supplied subject to change without notice. Specifications are typical at 24 V, 73°F and 50% RH unless otherwise stated.

General	
Product Operating Temperature	32°F to 120°F
Humidity	10% to 93% RH (no condensation or icing)
Standards and Approvals	UL, ULC, FM, CSFM
Dimensions	4.9" W x 4.9" H x 1.175" D
Materials	Housing: UL94 V-0 polycarbonate
Wire Size	12 - 24 AWG

LED Status		
LED Color	Description	XP95/Discovery Compatibility
Green	Polling	x
Yellow (solid)	Isolation	x
Red	Alarm	x

Single Line Circuit (SLC) - Supervised Power Limited	
Supply Voltage	17 V to 28 V DC
Modulation Voltage	5 V - 9 V peak to peak
Supervisory Current	500 μ A
Switch-on Surge Current	900 μ A
Alarm/Operated Current, LED ON	1.6 mA per LED
Maximum Loop Current	1 A

Initiating Device Circuit (IDC)	
Wiring Styles	Supervised power limited Class A and Class B
Voltage	3.3 V DC
Line Impedance	100 Ω Max
End-of-Line Resistors*	47 k Ω

*Note: A UL listed end-of-line resistor is available at Avenger - Part No. 44251-146

